## STEINMANS SAFETY BLIND - RAISED FACE OR PLAIN FACE FLANGES

Client Name:	Provided by: Steinmans, LLC	Item No.: SB-2500-04HF-0050-A36CS	Revision: REV-01
Company:	Prepared by: DSF	Design Type: STEINMANS Safety Blind	Date: 09/17/2010

Quantity: 1

Item Description: STEINMANS Safety Blind

Line Size. NPS: 1/2

Material of Blank/Spacer: ASTM A36 Carbon Steel Pl.

Flange Class Rating: Class 2500
Facing Type: Plain Face
Facing Finish: Mill Finish

\*Standards: (a) ASME B16.5 Flanges, NPS 1/2 thru 24

(b) ASME B16.48 Line Blanks(c) ASME B31.3 Process Piping

Dimensional Tolerance: +/- 0.03 in.

Thickness Tolerance: ASTM Plate Standard

Weight Density (lb/in^3): 0.289
Corrosion Allowance: 0.000 in.
Design Temperature: N/A

Allowable Pressures (psig): NOT RATED FOR PRESSURE

Construction of Design: One Piece Construction

Material of Handle/Web: N/A - Handle Not Separate (One Piece Construction)
Welding Requirements: No Welding Required (One Piece Construction)

Coating: Shop Paint (Flat Black)

Special Features: None

øG K K K

	Dimensions					
	Inch	mm				
L =	6.4	162				
W =	2.6	66				
N =	n/a	n/a				
G =	0.9	22				
F=	0.3	7				
B =	1.5	38				
K =	1.0	25				
T =	0.13	3				

Weight						
Lbs	kg					
0.5	0.2					

	Markings	l
Ī	STEINMANS	Ĭ.
I	A 36 - CS	ı
Ī	2500# 1/2	ĺ
Ī	1/8 THK	ĺ

Inverted Bottom Marking												
2500# 1/2												
Ι.	_	_	_	_	_	_	_	_	_	_	_	-

- Notes: (1) Marking: Safety Blanks shall be permanently marked as follows:
  - (a) STEINMANS
  - (b) Material specification and grade (abbreviated)
  - (c) Flange class (abbreviated)
  - (d) Pipe Size (NPS)
  - (e) Thickness (Inches)
  - (2) Hole size "G", shall be the same size as the flange bolt hole.
  - (3) Customer to provide all required design specifications prior to placing order. Design Specifications are as follows:
    - (a) Pipe Size, NPS
    - (b) Flange Class and type
    - (c) Material
    - (d) Special coatings (if any)
    - (e) Added corrosion thickness value (if any)
  - (4) Steinmans Safety Blinds are not designed to withstand high pressures and/or temperatures.

They are to be used for temporary line blocking for potential flow only. To be used in non-energized systems.

## STEINMANS, LLC

4142 Ogletown-Stanton Rd. Ste. 117

Newark, DE 19713 Phone: (302) 999-1784 Fax: (302) 999-1785 sales@steinmansllc.com

www.steinmansllc.com

Copyright (c) 2010 Steinmans, LLC. All Rights Reserved.